

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) A bookbinding apparatus comprising:
 - a movable adhesive tank constituted of a material containing a ferromagnetic material for retaining therein an adhesive melted by heat;
 - a roller rotatably supported with the adhesive tank so as to dip a lower portion thereof in the adhesive retained in the adhesive tank, for applying the adhesive to a sheet stack along a lateral edge thereof;
 - a holding unit capable of holding the sheet stack;
 - an adhesive tank carrier for disposing the adhesive tank and the roller at a stand-by position located outside a longitudinal end face of the sheet stack held by the holding unit in a stand-by stage, and moving the adhesive tank and the roller together from the stand-by position in a longitudinal direction of the sheet stack substantially through an entire area under a back face thereof in a bookbinding stage; and
 - a non-contact heater provided with an electromagnetic induction heating coil for contactlessly heating the adhesive tank disposed , and the non-contact heater is immovably placed at the stand-by position to melt the adhesive.

2. (Cancelled)

3. (Cancelled)

4. (Currently Amended) The bookbinding apparatus according to Claim ~~[[3]]~~ 1, wherein the adhesive tank is provided with a container-shaped main body of a non-ferromagnetic material for retaining therein the adhesive and a ferromagnetic heating portion located on an outer surface of the main body; and the non-contact heater is located so as to confront the heating portion of the adhesive tank placed at the stand-by position.

5. (Previously Presented) The bookbinding apparatus according to Claim 1, wherein the roller is constituted of a non-ferromagnetic material.

6. (Previously Presented) The bookbinding apparatus according to Claim 1, wherein the adhesive tank is provided with an inclined bottom wall in an adhesive retaining region of a container-shaped main body of the adhesive tank to retain the adhesive therein, for providing a deeper portion corresponding to a position of the roller.

7. (Previously Presented) The bookbinding apparatus according to Claim 1, wherein the adhesive tank is provided with a fin for promoting melting of the adhesive, erected on a bottom wall in the adhesive retaining region of the container-shaped main body of the adhesive tank to retain the adhesive therein.

8. (Previously Presented) The bookbinding apparatus according to Claim 1, further comprising:

an adhesive supply unit installed opposite to the stand-by position of the adhesive tank across the sheet stack, including a storing section for storing therein adhesive pellets to be transformed into the melted adhesive retained in the adhesive tank, a pellet supply path downwardly extending from a bottom portion of the storing section, and a pellet outlet through which the adhesive pellets transferred through the pellet supply path are discharged; and

an adhesive supply control unit for controlling a supplying timing of the adhesive pellets from the adhesive supply unit, such that a predetermined amount of adhesive pellets is discharged from the pellet outlet to the adhesive tank at a time that the adhesive tank has reached a position where the adhesive tank can receive the adhesive pellets discharged from the pellet outlet,

thereby the adhesive pellets supplied into the adhesive tank are melted.

9. (Previously Presented) The bookbinding apparatus according to Claim 8, further comprising:

a level detection unit for detecting a surface level of the adhesive retained in the adhesive tank;

wherein the adhesive supply control unit supplies the adhesive pellets until the adhesive surface exceeds a reference level, when the adhesive surface level has been detected to be lower than the reference level by the level detection unit.

10. (Previously Presented) The bookbinding apparatus according to Claim 8, further comprising:

two openable partition plates disposed inside the supply path with a predetermined interval therebetween, so that a predetermined amount of adhesive pellets are stored between the partition plates;

wherein the adhesive supply control unit open or close the two partition plates independently.

11. (Previously Presented) The bookbinding apparatus according to Claim 10, wherein each of the two partition plates is of a disk shape with an opening, and are fixed by a shaft disposed substantially parallel to the supply path such that a rotation phase of the opening of the respective partition plates is different from each other; and the adhesive supply control unit drives the shaft to rotate such that only one of the partition plates permits a communication through the supply path.

12. (Cancelled)

13. (Previously Presented) The bookbinding apparatus according to Claim 1, further comprising:

a binding mode selection unit for selecting a bookbinding mode according to a signal identifying whether a case binding mode of binding a sheet stack with a cover or a pad binding mode of binding a paper pad without a cover; and

a rotation control unit for switching a roller controlling mode according to the bookbinding mode selected by the bookbinding mode selection unit.

14. (Previously Presented) The bookbinding apparatus according to Claim 13, wherein the adhesive tank carrier serves to move the adhesive tank and the roller back and forth in a longitudinal direction of the sheet stack; and the rotation control unit rotates the roller in a forward direction with respect to a moving direction thereof, during both of the forward and backward travels of the adhesive tank, when a pad binding mode in which a cover is not provided to the sheet stack is selected by the bookbinding mode selection unit.

15. (Previously Presented) The bookbinding apparatus according to Claim 13, wherein the adhesive tank carrier serves to move the adhesive tank and the roller back and forth in a longitudinal direction of the sheet stack; and the rotation control unit rotates the roller in a different direction according to a moving direction thereof.

16. (Previously Presented) The bookbinding apparatus according to Claim 15, further comprising:

a thickness detecting device for detecting a thickness of the sheet stack held by the holding unit; wherein the rotation control unit stops a rotation of the roller during a forward travel of the adhesive tank but rotates the roller in a reverse direction with respect to the moving direction during a backward travel of the adhesive tank when a thickness of the sheet stack has been detected to be equal to or thinner than a reference thickness, while the rotation control unit rotates the roller in a forward direction with respect to a moving direction thereof during both of the

forward and backward travels of the adhesive tank, when a thickness of the sheet stack has been detected to be thicker than the reference thickness, in case where the case binding mode of providing a cover to the sheet stack is selected by the bookbinding mode selection unit.

17. (Previously Presented) The bookbinding apparatus according to Claim 16, wherein the reference thickness is in a range of 1.8 to 2.2 mm.

18. (Currently Amended) The bookbinding apparatus according to Claim 16, further comprising:

a position detection unit for detecting a position of the adhesive tank;

wherein, once the adhesive tank reaches a predetermined position during a backward travel of the adhesive tank, the rotation control unit stops the rotation of the roller during the subsequent travel of the adhesive tank from the predetermined position to a final edge of the sheet stack.